Origin: Customer:

PTS ÉLECTRIQUE Ltée
ISO 9001
20201 Clark Graham, Baie-D'Urfé, QC H9X 3T5
Tél: (514) 457-8886 / 1-800-363-8420 Fax: 514-457-6787
PTSELECTRIQUE.COM



ELECTRICAL PROPERTIES

Low Frequency Flashover Voltage
Wet: 125kV; Dry: 170kV
Critical Impulse Flashover Voltage
Pos.: 280kV; Neg.: 340kV
Low Frequency Withstand Voltage
Wet: 100kV; Dry: 120kV
Impulse Withstand Voltage: 250kV
Radio Influence Voltage Data:
Test Voltage to Ground: 30kV;
Maximum RIV at 1000kHz: 200μV

PHYSICAL PROPERTIES

Creepage Distance: 1092mm
Net weight: 28Kg

MECHANICAL PROPERTIES

Cantilever Strength Upright/Underhung: 17.8kN
Tension Strength: 111.2kN
Torsion Strength: 2260N·m
Compression Strength: 267kN

According to Standard Specification:
ANSI C 29.9 execpt drawing



SUZHOU PORCELAIN INSULATOR WORKS

Scale	1:2.5	SOLID CORE STATION POST INSULATOR	Designation	
Design	W.C.M		Cat.No.	TR267
Check	L.H.X		Drawing No.	347870E2
Approve	Z.Y.X		Issue	1
Date	1992.04.15			

		Approve
		Design
		modify
		Issue
		Approve
		Design
		modify
A		Issue